



NLS-FM305X-2X

FIXED MOUNT BARCODE SCANNER

FEATURES

- **Snappy On-screen Barcode Capture**

Armed with Newland's sixth-generation of **UIMG[®]** technology, the scanner excels at reading on-screen barcodes containing large amounts of data.

- **IR Trigger**

The IR sensor in the scanner exhibits an improved sensibility in activating the scanner to scan barcodes as they are presented, markedly increasing throughput and productivity.

- **Durable Metal Housing**

The scanner uses a durable metal housing, making it ideal for self-service applications.

- **Outstanding Power Efficiency**

The advanced **NDC** technology incorporated in the scanner helps reduce the power consumption and prolong the service life of the device..



CMOS



1D Barcode



2D Barcode



RS232



USB

NLS-FM305X-2X

Performance

		NLS-FM3056-2X	NLS-FM3051-2X
Image Sensor		752*480 CMOS	
Illumination		White LED	
Symbologies	2D	PDF417, Data Matrix, QR Code, Aztec, Micro QR	
	1D	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128 (FNC1, FNC2, FNC3), Code 93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GSI Databar (RSS-Expand, RSS-Limited, RSS-14), Code 39 (Code 39 FULL ASCII), Code 11, MSI-Plessey, Plessey, GSI-128 (UCC/EAN-128), AIM 128	
Resolution*		≥5mil	
Scan Mode		Sense mode, Continuous mode	
Scan Angle**		Roll: 360°, Pitch: ±40°, Skew: ±40°	
Min. Symbol Contrast*		25%	
Scan Window		31.5mm×46.5mm	38.3mm×60.4mm
Field of View		Horizontal: 75°, Vertical: 50°	

Physical

Interface		RS-232, USB	
Operating Voltage		5VDC±5%	
Rated Power Consumption		572mW (typical)	
Current@5VDC	Operating	115mA (typical), 198mA (max.)	
Dimensions		78.7(W)×67.7(D)×53(H)mm (max.)	78.7(W)×67.7(D)×62.5(H)mm (max.)
Weight		168g	184g
Notification		Beeper	

Environmental

Operating Temperature		-20°C to 60°C (-4°F to 140°F)	
Storage Temperature		-40°C to 70°C (-4°F to 158°F)	
Humidity		5% to 95% (non-condensing)	
ESD		±8 KV (air discharge); ±4 KV (direct discharge)	

Certificates

Certificates & Protection		FCC Part15 Class B, CE EMC Class B, RoHS
---------------------------	--	--

Accessories

Cable	USB	Used to connect the scanner to a host device.
	RS-232	Used to connect the scanner to a host device.
Power Adapter		DC5V power adapter to provide power for the scanner with RS-232 cable.

*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample printed barcodes made by Newland.

**Test conditions: Scan Distance= (min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp;

2D: QR Code; 10 Bytes; Resolution=15mil; PCS=0.8.

Specifications are subject to change without notice.

Version: V12

Newland AIDC

Add: No.1 Rujiang West Rd,
Mawei, Fuzhou, Fujian 350001, China
Tel: +86-591-83979500
Fax: +86-591-83979216
Email: info@nlsan.com
Web: www.newlandaidc.com

North America&Latin America

Add: 46559 Fremont Blvd,
Fremont, CA 94538, USA
Tel: +1 510 490 3888
Fax: +1 510 490 3887
Email: info@nlsan.com
Web: www.newlandamerica.com

Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,
The Netherlands
Tel: +31 (0) 345 87 00 33
Email: sales@newland-id.com
Tech Support: tech-support@newland-id.com
Web: www.newland-id.com

Asia Pacific

Taiwan:
Add: 7F-6, No. 268, Liancheng Rd,
Jhonghe Dist. 235, New Taipei City, Taiwan
Tel: +886 2 7731 5388
Email: info@newland-id.com.tw