



# **FEATURES**

# **Rugged Construction**

The NLS-WDI's rugged housing is sealed to IP67 standards for protection against dust and water and withstands 1.2m drops to concrete.

# O User-focused Ergonomics

The slim ergonomically designed body of the NLS-WDI makes it easy to wear it in your hand and reduces stress & fatigue during extended work sessions.

# **Diverse Wearable Solutions**

The NLS-WD1 can be connected to various Bluetooth peripherals to meet application needs like barcode scanning, UHF, print, etc. All these expand the working ability of the smart watch.

# **High-precision Sensor**

Armed with multiple sets of high-precision sensors, the NLS-WD1 can position the user's location and speed in real time.

# **Long-lasting Battery Life**

The NLS-WD1 is equipped with a 3300mAh battery that provides a full-shift battery life of up to 12 hours from a single charge.

# **Heavily Customized Android**

Heavily customized android operation system allows users to easily operate and execute applications.

# **Excellent Performance**

The NLS-WD1 is equipped with quad-core highperformance processor, 4G and 3+32 memory, providing faster and smoother performance all the

# **Corning Glass**

The dial plate adopts rugged corning glass which can provide high resistance to scratch and improve the drop performance.















# **NLS-WD1**

#### **Performance**

Processor 2.0 GHz, octa cores 64-bit processor

Operating System Android 9

3GB RAM. 32GB ROM Memory

Interface USB Type -C, battery charging over USB supported, OTG not supported

#### Physical/Electrical

Dimensions (L×W×H) Dial plate:  $77 \times 56$  (mm), the thickness of the dial plate: 17.8mm

Weight 143g

2.8" (640 × 480) capacitive touch screen, corning glass for the dial plate Display

Keypad 2keys (power key/lock screen key, user-defined key)

Vibrator, speaker, and LED Notification 3.8V, 3300mAh (non-removable) Battery 13 megapixels, auto focus; Camera

LED Flash, support torch mode

GPS GPS (AGPS), GLONASS, Beidou, Galileo Media Speaker \*1, dual microphone, noise reduction

Sensor Angular Velocity Sensor, Geomagnetic Sensor, Air Pressure Sensor, Acceleration Sensor

#### **Environmental**

Operating Temperature -20°C to 55°C (-4°F to 131°F) Storage Temperature -30°C to 70°C (-22°F to 158°F) Humidity 5% to 95% (non-condensing)

±10 kV (Air discharge), ±6 kV (Direct discharge) Static Discharge Drop 1.2m drops to concrete (for six sides, one drop per side)

# Wireless

WI AN RADIO Bands built-in 802.11 a/b/g/n/ac,, support 2.4G and 5G dual frequency

WWAN RADIO 2G GSM: 900/1800MHz 3G WCDMA (B1, B8) 4G TD-LTE (B34, B38, B40)

FDD-LTE (B1, B3, B7, B8, B20, B28)

WPAN RADIO

Bluetooth 5.0

# **Card Slot**

SIM Card. Nano SIM\*1

# Accessory (Optional)

#### AC adapter, cable

# Certificates&Protection

Certificates CE-RED

Specifications are subject to change without notice.

2022/01/21

Version: V1.3

#### **Newland AIDC**

Add: No.1 Rujiang West Rd., Mawei, Fuzhou, Fujian 350001, China Tel: +86-591-83979500 Fax: +86-591-83979216 Email: info@nlscan.com Web: www.newlandaidc.com

#### Asia Pacific

Taiwan: Add: 7F-6, No. 268, Liancheng Rd., Jhonghe Dist. 235, New Taipei City, Taiwan Tel: +886 2 7731 5388 Email: info@newland-id.com.tw

#### Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg, The Netherlands Tel: +31 (0) 345 87 00 33 Email: sales@newland-id.com Tech Support: tech-support@newland-id.com

#### North America & Latin America

Add: 46559 Fremont Blvd., Fremont, CA 94538, USA Tel: +1 510 490 3888 Fax: +1 510 490 3887 Email: info@nlscan.com

